

RT 390.01

Control valve, pneumatically driven, Kvs 2,5, equal-percentage



Learning objectives/experiments

- functional range of an electro-pneumatically operated control valve
- recording of the flow rate characteristic during the experiment (flow rate dependent on degree of opening)
- standard current signals and correct electrical wiring and interconnection

Specification

- [1] control valve as actuator in control loop
- [2] electro-pneumatic positioner to actuate the pneumatic control valve drive by an electrical signal
- [3] operating direction: rising
- [4] safety position: closed

Technical data

Control valve

- DN 20
- PN 16
- K_{vs} value: 2,5
- characteristic: equal-percentage

Actuator drive

- diaphragm area: 120cm²
- stroke: max. 15mm
- nominal signal range: 0,2...1bar
- electro-pneumatic positioner
 - ▶ input signal: 4...20mA

LxWxH: 500x260x410mm

Weight: approx. 10kg

Description

- industrial control valve with electro-pneumatic positioner
- used in the construction of level and flow rate control systems

The electro-pneumatic control valve is used primarily as the actuator in a level or flow rate control loop.

The control valve is installed and connected to the test stand for control valves, RT 390. An electrical signal input (identical to the controller output) is pre-configured and routed to the base module terminal array which is specific to the particular application.

The control valve is fitted with an electro-pneumatic positioner which requires a supply of compressed air. The valve rod is driven by a pneumatically operated membrane. The electro-pneumatic control valve is set to the safe "closed" position when no auxiliary power is applied.

Required for operation

Supply via RT 390

Scope of delivery

- 1 control valve with electro-pneumatic positioner
- 1 set of hoses with quick-release couplings für water connection
- 1 connecting cable for compressed air

RT 390.01

Control valve, pneumatically driven, Kvs 2,5, equal-percentage

Required accessories

RT 390 Test stand for control valves